

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

1. (Currently Amended) An image forming apparatus, comprising:
 - a first memory for storing image data;
 - an image input unit for inputting the image data to the first memory;
 - a second memory for storing image forming conditions, said image forming conditions being at least one of: number of copies, and magnification;
 - an image output unit for printing the image data stored in the first memory under the image forming conditions stored in the second memory;
 - a command unit for generating a command of discarding the image data being printed from the image output unit;
 - an image data discarding controller for discarding the image data stored in the first memory when the command of discarding the image data is generated by the command unit, while maintaining the associated image forming conditions stored in the second memory;
 - a job stopping controller for stopping a print operation of a job being printed by the image output unit; and
 - an output control unit for causing the output unit to automatically output image data newly input from the image input unit after the discarding of image data from the first memory under the maintained image forming conditions;

wherein the command unit generates a command of discarding the image data of the job stopped by the job stopping controller; and

wherein the image data discarding controller discards the image data of the job stopped by the job stopping controller and maintains the image forming conditions of the job.

2. (Canceled)

3. (Canceled)

4. (Previously Presented) The image forming apparatus as recited in claim 1, further comprising change means for changing the maintained image forming conditions.

5. (Canceled)

6. (Previously Presented) The image forming apparatus as recited in claim 1, wherein the image input unit is an image reader for reading the image from the original and acquiring the image data, wherein the image output unit and the image reader operate independently.

7. (Previously Presented) The image forming apparatus as recited in claim 6, wherein if the image reader is reading another original, the command unit

generates a command of suspending the reading operation, and at the same time, it generates a command of discarding the image data to be printed.

8. (Previously Presented) The image forming apparatus as recited in claim 6, wherein if the image reader is reading another original, the command unit generates a command of discarding the image data to be printed after the reading operation for another original has been completed.

9. (Original) The image forming apparatus as recited in claim 1, wherein the image output unit is a printer for printing an image on a paper based on the image data.

10. (Currently Amended) An image forming apparatus, comprising:
an image reader for reading an original and acquiring image data of the original;
an image memory for storing the image data acquired by the image reader;
a mode memory for storing image forming conditions selected for the acquired image data, said image forming conditions being at least one of: number of copies, and magnification;
a printer for printing an image on a paper, based on the image data stored in the image memory, under the image forming conditions stored in the mode memory;
a command unit for generating a command of discarding the image data being printed by the printer;

an image data discarding controller for discarding the image data stored in the image memory when the command of discarding the image data is generated by the command unit, while maintaining the associated image forming conditions stored in the mode memory;

a print control unit for causing the printer to automatically print another image data newly read by the image reader after the discarding of image data from the image memory under the maintained image forming conditions in the mode memory; and

a job stopping controller for stopping a print operation of a job being printed by the printer;

wherein the command unit generates a command of discarding image data of the job stopped by the job stopping controller; and

wherein the image data discarding controller discards the image data of the job stopped by the job stopping controller and maintains the image forming conditions of the job.

11. (Original) The image forming apparatus as recited in claim 10, further comprising changing means for changing the maintained image forming conditions.

12. (Original) The image forming apparatus as recited in claim 10, wherein the image reader and the printer operate independently, and the image memory stores image data for a plurality of jobs.

13. (Previously Presented) The image forming apparatus as recited in claim 12, wherein the print control means unit give priority to a new job for printing under the maintained forming conditions over the rest of the jobs on a waiting list.

14. (Previously Presented) The image forming apparatus as recited in claim 12, wherein if the image reader is reading another original, the command means unit generates a command of suspending the reading operation, and at the same time, it generates a command of discarding the image data to be printed.

15. (Previously Presented) The image forming apparatus as recited in claim 12, wherein if the image reader is reading another original, the command means unit generates a command of discarding the image data to be printed after the reading operation for another original has been completed.

16. (Currently Amended) An image forming method, comprising:
storing image data in an image memory;
storing image forming conditions for the image data in a memory, said image forming conditions being at least one of: number of copies, and magnification;
printing an image on a paper, based on the image data stored in the image memory, under the image forming conditions stored in the memory;
generating a command of discarding the image data whose image is being printed;

stopping a print operation of the image data being printed and erasing the image data from the image memory in response to the command, while maintaining the associated image forming conditions in the memory;

acquiring new image data and storing the new image data in the image memory; and

automatically printing a new image on a paper, based on the new image data acquired after the discarding of image data from the image memory, under the image forming conditions maintained in the memory.

17. (Original) The image forming method as recited in claim 16, further comprising the step of changing the maintained image forming conditions.

18. (Previously Presented) The image forming method as recited in claim 16, further comprising the step of printing image data of another print job on a waiting list after the newly acquired image data has completely been printed.

19. (Previously Presented) An image forming apparatus, comprising:
a first memory for storing image data;
a second memory for storing image forming conditions, said image forming conditions being at least one of: number of copies, and magnification;
an image output unit for printing image data stored in a first memory under the image forming conditions stored in the second memory;
a command unit for generating a command of discarding the image data being printed from the image output unit;

an image data discarding controller for discarding the image data stored in the first memory when the command of discarding the image data is generated by the command unit, while maintaining the associated image forming conditions stored in the second memory;

a job stopping controller for stopping a print operation of a job being printed by the image output unit;

wherein the command unit generates a command of discarding the image data of the job stopped by the job stopping controller; and

wherein the image data discarding controller discards the image data of the job stopped by the job stopping controller and maintains the image forming conditions of the job;

an image input unit for inputting image data to the first memory; and

an output control unit for causing the output unit to output image data newly input from the image input unit after the discarding of image data from the first memory under the maintained image forming conditions;

wherein the first memory stores a plurality of image data, and the output control unit gives priority to the newly inputted image data to be printed under the maintained image forming conditions over the rest of the image data.

20. (Previously Presented) The image forming apparatus of claim 1, wherein storing image forming conditions for the image data in a memory, said image forming conditions being at least one of: number of copies, magnification and paper size.

21. (Previously Presented) The image forming apparatus of claim 10, wherein storing image forming conditions for the image data in a memory, said image forming conditions being at least one of: number of copies, magnification and paper size.

22. (Previously Presented) The image forming method of claim 16, wherein storing image forming conditions for the image data in a memory, said image forming conditions being at least one of: number of copies, magnification and paper size.

23. (Previously Presented) The image forming apparatus of claim 19, wherein storing image forming conditions for the image data in a memory, said image forming conditions being at least one of: number of copies, magnification and paper size.